

AquaProof RC

Rubberised Bitumen waterproofing coating

DESCRIPTION:

A rubberised bitumen emulsion which dries to a tough, black coating providing a highly effective cold-applied, damp-proof membrane. It can also be used as a waterproof for floors, walls and other above ground structures. It is equally effective as an adhesive for wood blocks, wood mosaic panels. It can also be applied to damp surfaces. Resistant to extreme heat and cold.



USES:

- ▶ Cold applied. ▶ Single component, easy to apply.
- ▶ Can be applied on damp substrates. ▶ Asbestos free, odorless. ▶ Can be applied in closed or confined spaces.
- ▶ Solvent free & environmentally friendly. ▶ Good resistance against chloride and sulphate ions.
- ▶ Has good adhesion to most building substrates. ▶ Seamless/joint free.

PREPARATION OF SURFACE:

The surface to be treated should be clean, dry and free from dirt, dust, oil and grease. All major cracks should be filled up with repair mortar. Nail heads and other protrusions that are likely to damage the coating must be removed or grounded.

METHOD OF APPLICATION:

Normally, Priming is not required however priming the surface is recommended when the surface is very dry and porous. The priming coat is made by diluting AquaProof RC with 40 - 50% clear compatible water. AquaProof RC may be applied with Brush / Roller / Spray Machine on the prepared surface. Stir well before use, replace lid when not in use. For any spillage soak up with sand or sawdust and wash down immediately

STORAGE:

AquaProof RC has shelf life of 12 Months in sealed condition, It must be store in shaded area having temperature ranging 5 °C to 50 °C

PACKING: 18 KG, 200 KG

Corporate Office: 54-E, Mohafiz Town, Multan Road Lahore - Pakistan. Tel: +92 42 35457688-35457699 Fax: +92 42 35457689

Islamabad Office:
1-km, Malang Jan Street, G.T
Road, Zahidabad Tarnol,
Islamabad.
Tel: +92 51 2256421
Cell: 0302-8551907

Karachi Office:
House No C-13,
Block-B, Gulshan-e-jamal,
Karachi.
Tel: +92 21 34583591

Faisalabad Office:
82-B, Commercial Center,
Millat Chowk, Faisalabad.
Tel: +92 41 8580233

Peshawar Office:
New Akbar Market,
Room # 14,1st Floor,
Achani Chowk, Ring Road,
Peshawar.
Cell: 0301-8551907



PRODUCT SPECIFICATION	
Residue Spaces	Rubberised Bitumen
Over coating time	Minimum 2 hours
Appearance	Dark brown liquid
Drying time after application	120 minutes @35°
Specific gravity	1.02
Coverage	2 m ² /kg - 3m ² /kg

CONTACT:



ROOFGRIP

Reinforced Waterproofing System

AquaProof RC

Rubberised Bitumen waterproofing coating

دیرپا
واٹر پروفنگ

گرم ٹک کا متبادل

تگانی
میں آسان

انتہائی
لچکدار

ماحول
دوست

پانی کے اثرات کے خلاف
بہترین تحفظ

موثر چپکنے کی
صلاحیت